

MATERIAL SAFETY DATA SHEET

Manufacturer's Name:

Flame Safe Wood Products, Inc.
2653 Warfield Avenue
Fort Worth, Texas 76106

Emergency Telephone No.

(800) 424-9300 CHEMTRIC

Information Telephone No.

(817) 740-9197 (800) 333-9197

SECTION I - PRODUCT IDENTIFICATION

Product Name and Synonyms: Flame Safe X-T Vacuum/Pressure Treated Wood

SECTION II - HAZARDOUS INGREDIENTS

Component (Gas Registry No.)	Weight Percent	AGIH TLV	OSHA PEL
Proprietary (00764-38-2)	15.3%	1ppm TWA 3PPM stel	1ppm TWA

SECTION III - PHYSICAL PROPERTIES

Appearance and Odor: wood, yellowish, odor-pine

Molecular Weight: Not Applicable

Boiling Point: N/N

Vapor Pressure: (mm of Mercury) Not Determined

Melting Point: (Degrees Fahrenheit) N/A

Specific Gravity (water=1) 1.120 - 1.160

Vapor Density: (air = 1)N/A

PH: 5.2 - 5.8

Evaporation Rate: (Butyl Acetate=1; Not determined. (<1) slower

Percent Volatile (by weight):

Solubility in Water: Moderate

SECTION IV - FIRE AND EXPLOSION DATA

Flash point (Degrees Fahrenheit: Pensky-Martins Closed Sup): N/A

Fire Extinguishing Media: Water, CO₂, foam, standard firefighting materials

Flammable Limits (Percent by Volume): None flammable

Special Fire Fighting Procedures and Equipment: CO₂, water particulate matter and nitrogen

Unusual Fire and Explosion Hazards: None

Hazardous Combustion Products: Trace amounts,CO₂, water, particulate matter and nitrogen

SECTION V - REACTIVITY DATA

Stability: Stable

Conditions to Avoid: None Known

Incompatibility (Materials to Avoid): None known

Hazardous Polymerization: Will NOT occur

Hazardous Decomposition Products: From wood CO₂, water particulate, matter

SECTION VI - HEALTH AND HAZARD INFORMATION

Health Hazards (acute and chronic): None known

OHSA Regulated: No

Carcogenicity: Wood Dust

Emergency and First Aid Procedures:

If ingested, seek medical attention. Wash skin with soap and water

Signs and Symptoms of Exposure:

Sawdust may irritate some sensitive persons. Practice good hygiene.

SECTION VII - SPECIAL PROTECTION INFORMATION**Protective Gloves:** Wear gloves to avoid splinters**Eye Protection:** Safety goggles or goggles to protect against sawdust and flying wood particles.**Respiratory Protection (Specify Type)** Use NIOSH/MSHA approved Dust/Mist respirator when sawing or machining, but not required unless wood dust PEL of 5 mg/m³ exceeded**Ventilation:** Local Exhaust
Mechanical (general)
Special - Not applicable**Other Protective Equipment:** Any typical with any wood working**SECTION VIII - SPILL, LEAK, AND DISPOSAL PROCEDURES****Steps to be taken in case material is released or spilled:** Good housekeeping techniques.**Waste Disposal Methods:** Approved landfill**Precautions to be taken in Handling and Storing:** Store above ground. Product is shipped dry and should not be exposed to the weather**Other Precautions:** Keep Dry**SECTION IX - REGULATORY INFORMATION****NTP:** No**DOT:** Not regulated 49 CFR**OSHA (carcinogen):** No**IARC (nonographs):** No**EPA Hazardous Substance:** None 40 CFR 116-117

ACGH (TLV list): NO

TSCA: No Applicable information found**Effective Date:** October 1, 1997**Supersedes:** All previous**Important:** The information and data herein are believed to be accurate and have been compiled from sources believed to be reliable. It is offered to your consideration, investigation and verification. Buyer assumes all risk of use, storage, and handling of the product in compliance with applicable federal, state, and local laws and regulations.

FLAME SAFE WOOD PRODUCTS, INC. MAKES NO WARRANTY OF ANY KIND, EXPRESSED OR IMPLIED, CONCERNING THE ACCURACY OR COMPLETENESS OF THE INFORMATION AND DATA HEREIN.

Flame Safe Wood Products, Inc. will not be liable for claims relating to any party's use or reliance on information and data contained herein regardless of whether it is claimed that the information and data are inaccurate, incomplete, or otherwise misleading.